

U.S. SEAL MFG.

Use the Right Seal Installation Lubricant
so your seals don't end up looking like these.



PTFE or Silicone Based Lubricants Damage Seals

USE THE WRONG LUBE . . . GET THE WRONG RESULTS

Silicone or PTFE based lubricants are a poor choice when installing mechanical seals.

During seal installation, lubricants can come in contact with the sealing faces. Silicone or PTFE based products are very difficult to remove from these faces.

When the pump is started, these products draw the carbon from the primary ring, transfers the material onto the mating ring face, causing a build up which leads to premature seal failure.

USE THE RIGHT LUBE . . . GET THE RIGHT RESULTS

U.S. SEALUBE is a water based formula specifically designed to lubricate rubber, allowing for fast and easy seal installations.

It provides a high degree of lubricity to all rubber components but unlike PTFE or silicone based lubricants, U.S. SEALUBE evaporates, allowing the elastomer to grip the shaft or bore. Elastomers are left dry to the touch. The lubricity is gone and will not return even in the presence of moisture.

Your seal is now locked in place.

U.S. SEALUBE

- Safe for incidental food contact and potable water applications.
- Meets FDA Regulation 21 CFR 178.3570 and is NSF-Registered as a H1 lubricant.
- Great for all seals and elastomers.
- 15 to 20 minutes work time before drying.
- Totally evaporates, leaving no residue.

U.S. Seal Mfg. Part No.	Available In
LUBE-PP	1 cc Pillow Pak
LUBE-10ML	10 ml Tube
LUBE-05OZ	1/2 oz. Bottle
LUBE-4OZ	4oz. Bottle
LUBE-8OZ	8oz. Bottle



400-A Apgar Drive • Somerset, NJ 08873
Tel 800-243-5489 • Fax 877-849-7325
www.ussealmfg.com

VGS
VALUE GUARD SEAL